










General Tolerances acc to: ISO 2768-1 medium	File Name: SAMD 4 head scale.icd			Last saved: 2025/02/19 10:41	
	IRONCAD 2D drawing		Scale: 1:30	Drawn by:	Created Date:
 A4  ISO E		4 head scale - cover			Sheet No: 1 (4)
					Rev. ...
					Doc. No: SAMD scale




Item No.	PartName	Qty	Description
1	Stand	1	Frame for mounting chute and cut-gates
2	Dust extraction complete	1	Can be conencted to dust extraction system
3	Door frame	2	Basic frame for guarding
4	Door	4	Guards / covers / doors
5	2kg bucket complete	4	Weighing bucket assembly
6	Cut gate complete	4	Filler assembly w ith tw o-stage cut gate
7	Frame	1	Main machine frame / base
8	Leg	4	For applications w here no mezannine floor is available
9	Shoulder chute	1	Outfeed chute connects to FFS forming shoulder
10	Diverter complete	1	4 way chute with shot-off gates
11	Infeed chute	1	Supply holding hopper


General Tolerances acc to: ISO 2768-1 medium	File Name: SAMD 4 head scale.icd			Last saved: 2025/02/19 10:41	
	IRONCAD 2D drawing		Scale: 1:37	Drawn by:	Created Date:
 A4  ISO E		4 head scale - overview			Sheet No: 2 (4)
					Rev. ...
					Doc. No: SAMD scale



General Tolerances acc to:	File Name: SAMD 4 head scale.icd			Last saved: 2025/02/19 10:41	
	ISO 2768-1 medium	IRONCAD 2D drawing	Scale: 1:35	Drawn by:	Created Date:
				Sheet No: 3 (4)	Rev. ...
				Doc. No: SAMD scale	



Dust extraction system




Easy adjustment for fine-tuning

Cylinder with bellows on shaft for dust protection / longevity

Long lasting, maintenance free IGUS flange bearings on all pivot point

2 stage cut-gate for accurate filling




Calibration plate - easy calibration process

Guard for load-cell protection

Secure shut-off - no product leakage

Special scraper seals for dust protection / longevity




Smooth transition points to prevent product build-up

Shut off gates for cleaning / maintenance

Other features include:

- Able to be retro-fitted to replace volumetric filling systems on all types of VFFS machines.
- Full 316SS construction.
- 7" touch screen controller with easy recipe change over. No mechanical change-over parts needed.
- Speeds on 4 head machine up to 45 bpm depending on target weight.
- $\pm 0.4\%$ accuracy according to target weight.
- Auto adjustment calculation after every discharge automatically changes in-flight value to continuously increase accuracy and negae bulk density changes.

General Tolerances acc to: ISO 2768-1 medium	File Name: SAMD 4 head scale.icd			Last saved: 2025/02/19 10:41	
	IRONCAD 2D drawing		Scale: :	Drawn by:	Created Date:
  ISO E	4 head scale - features			Sheet No: 4 (4)	Rev. ...
				Doc. No: SAMD scale	